

## PK2150-31ST



<b>Display</b>	Size	15" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	350
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
<b>Communication Interface</b>	Micro-SD Slot	N/A
	USB Client	Yes
	USB Host	Yes
	Serial (DB9)	<b>COM1</b> RS232
		<b>COM2</b> RS422/RS485
<b>COM3</b> RS485		
Ethernet	YES(10/100Mbps)	
<b>Power</b>	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
<b>Environment</b>	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
<b>Dimension</b>	Dimension WxHxD (mm)	399.1 x 297.6 x 57.5
	Cutout Dimension WxH (mm)	384.5 x 283.0
	Net Weight (kg)	3 KG