

## PX150-XSD4B



<b>Display</b>	Size	15" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	50000
	Display Contrast	700
	Luminance (cd/m2)	350
	Operation	RTOS
	Touch Panel	5 Wire Analog Touch Panel
	CPU	CPU RISC ARM11 800MHZ
	Backup SRAM	1 MB
	Working Memory	256 MB
	Built-in Storage	1 GB
Real Time Clock (RTC)	Yes	
<b>Communication Interface</b>	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	<b>COM1</b> RS232/RS422/RS485
		<b>COM2</b> RS232/RS485
<b>COM3</b> RS232		
Ethernet	YES(10/100Mbps)	
<b>Power</b>	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
<b>Environment</b>	Operating Temperature	-20°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
<b>Dimension</b>	Dimension WxHxD (mm)	399.1 x 297.6 x 55
	Cutout Dimension WxH (mm)	384.5 x 283.0
	Net Weight (kg)	2.68 KG