

Report No.: T190625D08-I-F

Ref. No.: T190111D10-F

Page: 1 / 31  
Rev.: 01

## FCC TEST REPORT

for

### LCD Touch Control Panel

**MODEL: PT2104; KT2104; GT2104; MMPT2104; xPT2104; MT2104; FT2104;  
FC2104; DAK-2104B; LUI2104; MG-T2104-24; SK2104; eV2104; MT2104; TV2104;  
AST-2104THSxx; VT92104T; PY2104-AST; PSST2104-AST; PT2104-AST;  
KT2104-AST; ET2104-AST; ET2104-AST; THM2104A; MZ600-TT2104H;  
VM12104-AST; VM12104-AS; VM12104-AH; RT2104; RL2104; KT2104; PL2104;  
KL2104; AS43TFT1025; WOP-2100T; GPT2104; XI33B-T2B; xPT2104; HT2104;  
AS46TFT1007; CPT2104; PMT2104; IPT2104; IV214M-SEAP; IHM104T2E;  
IM-PT2104**

Issued to:

**Cermate Technologies Inc.**

**7F.-1, No.168, Liancheng Rd., Zhonghe Dist.,  
New Taipei City 23553, Taiwan (R.O.C.)**

Issued by:

**Compliance Certification Services Inc.**

**Xindian Lab.**

**No.163-1, Jhongsheng Rd., Xindian Dist.,  
New Taipei City, 23151 Taiwan.**

**TEL: 886-2-22170894**

**FAX: 886-2-22171029**

**Issued Date: August 2, 2019**

**Note:** This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



**Report No.:** T190625D08-I-F

**Ref. No.:** T190111D10-F

Page: 2 / 31

Rev.: 01

**Revision History**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	February 11, 2019	Initial Issue	ALL	Eva Fan
01	August 2, 2019	Add models	ALL	Eva Fan



Report No.: T190625D08-I-F

Ref. No.: T190111D10-F

Page: 3 / 31  
Rev.: 01

## TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION.....</b>	<b>4</b>
<b>2</b>	<b>EUT DESCRIPTION.....</b>	<b>5</b>
<b>3</b>	<b>TEST METHODOLOGY.....</b>	<b>6</b>
3.1.	DECISION OF FINAL TEST MODE .....	6
3.2.	EUT SYSTEM OPERATION .....	6
<b>4</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
4.1.	DESCRIPTION OF SUPPORT UNITS .....	7
4.2.	CONFIGURATION OF SYSTEM UNDER TEST .....	7
<b>5</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1.	FACILITIES .....	8
5.2.	ACCREDITATIONS.....	8
5.3.	MEASUREMENT UNCERTAINTY .....	8
<b>6</b>	<b>CONDUCTED EMISSION MEASUREMENT .....</b>	<b>9</b>
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
6.2.	TEST INSTRUMENTS .....	9
6.3.	TEST PROCEDURES.....	10
6.4.	TEST SETUP .....	11
6.5.	DATA SAMPLE .....	11
6.6.	TEST RESULTS .....	12
<b>7</b>	<b>RADIATED EMISSION MEASUREMENT .....</b>	<b>16</b>
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT .....	16
7.2.	TEST INSTRUMENTS .....	17
7.3.	TEST PROCEDURES.....	18
7.4.	TEST SETUP .....	19
7.5.	DATA SAMPLE .....	20
7.6.	TEST RESULTS .....	21
<b>8</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>27</b>
	<b>APPENDIX 1 - PHOTOGRAPHS OF EUT .....</b>	<b>A1-1</b>

# 1 TEST RESULT CERTIFICATION

**Product:** LCD Touch Control Panel

**Model:** PT2104; KT2104; GT2104; MMPT2104; xPT2104; MT2104; FT2104; FC2104; DAK-2104B; LUI2104; MG-T2104-24; SK2104; eV2104; MT2104; TV2104; AST-2104THSxx; VT92104T; PY2104-AST; PSST2104-AST; PT2104-AST; KT2104-AST; ET2104-AST; ET2104-AST; THM2104A; MZ600-TT2104H; VM12104-AST; VM12104-AS; VM12104-AH; RT2104; RL2104; KT2104; PL2104; KL2104; AS43TFT1025; WOP-2100T; GPT2104; XI33B-T2B; xPT2104; HT2104; AS46TFT1007; CPT2104; PMT2104; IPT2104; IV214M-SEAP; IHM104T2E; IM-PT2104

**Brand:** Cermate

**Applicant:** Cermate Technologies Inc.  
7F.-1, No.168, Liancheng Rd., Zhonghe Dist.,  
New Taipei City 23553, Taiwan (R.O.C.)

**Manufacturer:** Cermate Technologies Inc.  
7F.-1, No.168, Liancheng Rd., Zhonghe Dist.,  
New Taipei City 23553, Taiwan (R.O.C.)

**Tested:** January 15, 2019


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 6-2016 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit

## Statements of Conformity

Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.


The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Approved by:**



Sam Hu  
Assistant Manager

**Reviewed by:**



Eva Fan  
Supervisor of report document dept.

## 2 EUT DESCRIPTION

<b>Product</b>	LCD Touch Control Panel
<b>Brand Name</b>	Cermate
<b>Model</b>	PT2104; KT2104; GT2104; MMPT2104; xPT2104; MT2104; FT2104; FC2104; DAK-2104B; LUI2104; MG-T2104-24; SK2104; eV2104; MT2104; TV2104; AST-2104THSxx; VT92104T; PY2104-AST; PSST2104-AST; PT2104-AST; KT2104-AST; ET2104-AST; ET2104-AST; THM2104A; MZ600-TT2104H; VM12104-AST; VM12104-AS; VM12104-AH; RT2104; RL2104; KT2104; PL2104; KL2104; AS43TFT1025; WOP-2100T; GPT2104; XI33B-T2B; xPT2104; HT2104; AS46TFT1007; CPT2104; PMT2104; IPT2104; IV214M-SEAP; IHM104T2E; IM-PT2104
<b>Applicant</b>	Cermate Technologies Inc.
<b>Housing material</b>	Plastic w/ Metal plate
<b>Identify Number</b>	T190111D10
<b>Received Date</b>	January 11, 2019
<b>EUT Power Rating</b>	24VDC from DC Power Supply

### Model Differences

Model	Difference	Tested (Check)
PT2104	Original	<input checked="" type="checkbox"/>
KT2104; GT2104; MMPT2104; xPT2104; MT2104; FT2104; FC2104; DAK-2104B; LUI2104; MG-T2104-24; SK2104; eV2104; MT2104; TV2104; AST-2104THSxx; VT92104T; PY2104-AST; PSST2104-AST; PT2104-AST; KT2104-AST; ET2104-AST; ET2104-AST; THM2104A; MZ600-TT2104H; VM12104-AST; VM12104-AS; VM12104-AH; RT2104; RL2104; KT2104; PL2104; KL2104; AS43TFT1025; WOP-2100T; GPT2104; XI33B-T2B; xPT2104; HT2104; AS46TFT1007; CPT2104; PMT2104; IPT2104; IV214M-SEAP; IHM104T2E; IM-PT2104	For marketing purpose only.	<input type="checkbox"/>

### I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. COM 1 / COM 3 Port	1	1
2. COM 2 Port	1	1
3. USB Port	2	2
4. LAN Port	1	1
5. SD Card Slot	1	1

**Note:** Client consigns only one model sample to test (Model Number: PT2104).

### 3 TEST METHODOLOGY

#### 3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

**Conduction Modes:**

1	AC Power Mode
2	DC Power Mode

**Radiation Mode:**

1	Normal Mode
	Normal Mode / 1-18GHz

**Worst:**

**Conduction:** Mode 2

**Radiation:** Mode 1

#### 3.2. EUT SYSTEM OPERATION

1. Windows 10 boots system.
2. Press the start menu, select executive and type ping 192.168.10.10 -t (Server Notebook).

**Note:** Test program is self-repeating throughout the test.

## 4 SETUP OF EQUIPMENT UNDER TEST

### 4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


#### Peripherals Devices:

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	USB HDD	HD-234	N/A	N/A	A-Tec	Shielded, 1.8m with a core	N/A
2	LCD Touch Control Panel	PA2071	N/A	N/A	Cermate	COM: Shielded, 2.0m COM: Shielded, 3.0m	Unshielded, 1.4m
3	DC Power Supply	NES-35-24	N/A	N/A	MEAN WELL	Unshielded, 1.4m	Unshielded, 1.4m
4	SD Card	N/A	N/A	N/A	PQI	N/A	N/A
5	Server Notebook	XPS13	7R0S3G2	DOC BSMI: R31199	DELL	Unshielded, 20m	Unshielded, 1.8m
6	USB Cable	N/A	N/A	N/A	N/A	Shielded, 1.8m	N/A

#### Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 4.2. CONFIGURATION OF SYSTEM UNDER TEST



## 5 FACILITIES AND ACCREDITATIONS

### 5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

### 5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

### 5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	± 2.8
Radiated emissions	30MHz ~ 1000MHz	± 5.3
	1000MHz ~ 18000MHz	± 4.7
	18000MHz ~ 40000MHz	± 4.1

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be based on the results of the compliance measurement. Consequently the measured emissions being less than the maximum allowed emission result in this being a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is based on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.6dB and 5.2dB respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.



## 6 CONDUCTED EMISSION MEASUREMENT

### 6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 6.2. TEST INSTRUMENTS

Conducted Emission room # A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
BNC CABLE	EMEC	EMG178	BNC#A9	03/26/2019
EMI Test Receiver	R&S	ESCI	101201	09/25/2019
LISN	Schwarzbeck	NNLK 8129	8129-286	08/09/2019
LISN(EUT)	Schwarzbeck	NSLK 8127	8127527	08/09/2019
Pulse Limiter	R&S	ESH3Z2	SD-C002	08/15/2019
Thermo-Hygro Meter	Wisewind	201A	No. 02	05/06/2019
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.

### 6.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)


#### **Procedure of Preliminary Test**

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

#### **Procedure of Final Test**

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

## 6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1


Freq. = Emission frequency in MHz  
 Reading = Uncorrected Analyzer/Receiver reading  
 Factor = Insertion loss of LISN + Cable Loss + Pulse Limit  
 Result = Reading + Factor  
 Limit = Limit stated in standard  
 Margin = Reading in reference to limit  
 P = Peak Reading  
 Q = Quasi-peak Reading  
 A = Average Reading  
 L1 = Hot side  
 L2 = Neutral side

### Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

## 6.6. TEST RESULTS


Model No.	PT2104	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 63% RH	Test Mode	Mode 1
Tested by	Kevin Chang	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2779	42.26	9.95	52.21	79.00	-26.79	P	L1
0.4660	36.03	9.97	46.00	79.00	-33.00	P	L1
1.1180	34.62	10.01	44.63	73.00	-28.37	P	L1
1.7660	33.62	10.06	43.68	73.00	-29.32	P	L1
16.1700	43.73	10.68	54.41	73.00	-18.59	P	L1
25.2900	45.36	10.98	56.34	73.00	-16.66	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Model No.	PT2104	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 63% RH	Test Mode	Mode 1
Tested by	Kevin Chang	Phase	L2
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1860	32.70	9.94	42.64	79.00	-36.36	P	L2
0.2779	41.88	9.96	51.84	79.00	-27.16	P	L2
0.4660	35.84	9.97	45.81	79.00	-33.19	P	L2
1.7620	33.63	10.05	43.68	73.00	-29.32	P	L2
15.8460	43.58	10.65	54.23	73.00	-18.77	P	L2
25.4180	45.85	10.98	56.83	73.00	-16.17	P	L2

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Model No.	PT2104	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 63% RH	Test Mode	Mode 2 / Worst
Tested by	Kevin Chang	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2100	48.22	9.93	58.15	79.00	-20.85	P	L1
0.2779	39.22	9.95	49.17	79.00	-29.83	P	L1
0.3500	35.31	9.96	45.27	79.00	-33.73	P	L1
4.3900	48.02	10.21	58.23	73.00	-14.77	P	L1
10.0340	46.47	10.48	56.95	73.00	-16.05	P	L1
19.1580	33.01	10.77	43.78	73.00	-29.22	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Model No.	PT2104	6dB Bandwidth	9 kHz
Environmental Conditions	22°C, 63% RH	Test Mode	Mode 2 / Worst
Tested by	Kevin Chang	Phase	L2
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2100	48.51	9.94	58.45	79.00	-20.55	P	L2
0.2779	39.55	9.96	49.51	79.00	-29.49	P	L2
0.3500	35.67	9.96	45.63	79.00	-33.37	P	L2
4.3980	47.59	10.18	57.77	73.00	-15.23	P	L2
9.9819	46.69	10.44	57.13	73.00	-15.87	P	L2
19.6060	32.48	10.77	43.25	73.00	-29.75	P	L2

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

## 7 RADIATED EMISSION MEASUREMENT

### 7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

(3) The measurement above 1GHz is at close-in distances 3m, and determine the limit  $L_2$  corresponding to the close-in distance  $d_2$  by applying the following relation:  $L_2 = L_1 (d_1/d_2)$ , where  $L_1$  is the specified limit in microvolts per metre (uV/m) at the distance  $d_1$  (10m),  $L_2$  is the new limit for distance  $d_2$  (3m).

So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80



According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

## 7.2. TEST INSTRUMENTS

Open Area Test Site # H				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Bilog Antenna	Teseq	CBL 6112D	36995	06/25/2019
Cable	EMEC	CFD400NL-LW	N-Type#H11	08/15/2019
EMI Test Receiver	R&S	ESCI	101340	03/26/2019
Pre-Amplifier	HP	8447D	1937A01554	09/27/2019
Thermo-Hygro Meter	Wisewind	201A	No. 03	05/27/2019
Test S/W	EZ-EMC			
Above 1GHz Used				
Horn Antenna	ETS	3117	00139062	09/13/2019
K-Type Cable x 1m (1-40GHz)	Rosnol	K1K50-UP0264- K1k50-1M	160215-1	11/26/2019
Microflex Cable x 7m (1-18GHz)	Rosnol	A1K50-EW0630- A1k50-700CM	SD-R028	11/26/2019
Pre-Amplifier	HP	8449B	3008A01266	11/25/2019
Signal Analyzer	Agilent	N9010A	MY53440125	12/25/2019
Thermo-Hygro Meter	Wisewind	N/A	SD-R027	09/26/2019
Test S/W	EZ-EMC			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.

### 7.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)

#### Procedure of Preliminary Test


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

#### Procedure of Final Test


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

## 7.4. TEST SETUP

### Below 1GHz



### Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 7.5. DATA SAMPLE

### Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

### Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz  
 Reading = Uncorrected Analyzer/Receiver reading  
 Factor = Antenna Factor + Cable Loss - Amplifier Gain  
 Result = Reading + Factor  
 Limit = Limit stated in standard  
 Margin = Reading in reference to limit  
 P = Peak Reading  
 Q = Quasi-peak Reading  
 A = Average Reading  
 H = Antenna Polarization: Horizontal  
 V = Antenna Polarization: Vertical


### Calculation Formula

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

## 7.6. TEST RESULTS

### Below 1GHz

Model No.	PT2104	Test Mode	Mode 1
Environmental Conditions	25°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kevin Chang
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
80.3500	46.80	-13.58	33.22	40.00	-6.78	100	133	Q	V
272.4600	35.90	-6.56	29.34	47.00	-17.66	100	256	Q	V
463.4900	39.20	-1.49	37.71	47.00	-9.29	400	254	Q	V
517.8600	37.80	-0.58	37.22	47.00	-9.78	400	265	Q	V
573.3400	34.90	0.57	35.47	47.00	-11.53	400	271	Q	V
900.0300	33.80	4.00	37.80	47.00	-9.20	400	203	Q	V

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

<b>Model No.</b>	PT2104	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	25°C, 60% RH	<b>6dB Bandwidth</b>	120 kHz
<b>Antenna Pole</b>	Horizontal	<b>Antenna Distance</b>	10m
<b>Detector Function</b>	Quasi-peak.	<b>Tested by</b>	Kevin Chang
<b>Standard</b>	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
80.6500	36.80	-13.58	23.22	40.00	-16.78	400	105	Q	H
299.9400	35.20	-5.94	29.26	47.00	-17.74	400	135	Q	H
463.4600	36.70	-1.49	35.21	47.00	-11.79	100	45	Q	H
600.0200	33.80	0.38	34.18	47.00	-12.82	100	124	Q	H
654.5300	34.20	1.39	35.59	47.00	-11.41	100	121	Q	H
872.8200	32.20	3.62	35.82	47.00	-11.18	100	247	Q	H

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.  
2. P= Peak Reading; Q= Quasi-peak Reading.

## Above 1GHz


Model No.	PT2104	Test Mode	Mode 1
Environmental Conditions	23°C, 60% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical	Antenna Distance	3m
Highest frequency generated or used	300MHz	Upper frequency	18000MHz
Detector Function	Peak and average.	Tested by	Kevin Chang
Standard	FCC CLASS A		



Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
2091.667	45.38	-2.19	43.19	80.00	-36.81	P	V
2575.000	45.59	-1.94	43.65	80.00	-36.35	P	V
3700.000	45.87	-0.60	45.27	80.00	-34.73	P	V
4550.000	44.87	1.32	46.19	80.00	-33.81	P	V
5091.667	44.71	1.36	46.07	80.00	-33.93	P	V
5591.667	44.41	1.89	46.30	80.00	-33.70	P	V

Note: 1. P= Peak Reading; A= Average Reading.

Model No.	PT2104	Test Mode	Mode 1
Environmental Conditions	23°C, 60% RH	6dB Bandwidth	1 MHz
Antenna Pole	Horizontal	Antenna Distance	3m
Highest frequency generated or used	300MHz	Upper frequency	18000MHz
Detector Function	Peak and average.	Tested by	Kevin Chang
Standard	FCC CLASS A		




Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1891.667	45.57	-3.31	42.26	80.00	-37.74	P	H
2550.000	46.48	-1.95	44.53	80.00	-35.47	P	H
2958.333	47.55	-1.64	45.91	80.00	-34.09	P	H
4225.000	44.92	0.62	45.54	80.00	-34.46	P	H
4758.333	44.83	1.31	46.14	80.00	-33.86	P	H
5850.000	44.01	2.43	46.44	80.00	-33.56	P	H

Note: 1. P= Peak Reading; A= Average Reading.




## 966 Chamber Test Data

Job No.:	T190111D10	Polarization:	Vertical
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	24VDC
Test item:	Radiation Test	Date:	2019/1/15
Company:	Cermate Technologies Inc.	Time:	下午 06:30:44
Model:	PT2104	Temp.(°C)/Hum.(%)	23(°C)/60%
Description:	Normal Mode	Engineer Signature:	Kevin Chang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	80.4400	62.31	-24.10	38.21	40.00	-1.79	peak	
2	272.5000	50.99	-20.72	30.27	47.00	-16.73	peak	
3	463.5900	57.05	-16.76	40.29	47.00	-6.71	peak	
4	517.9099	55.49	-16.27	39.22	47.00	-7.78	peak	
5	573.2000	49.98	-15.30	34.68	47.00	-12.32	peak	
6	900.0900	48.47	-7.51	40.96	47.00	-6.04	peak	

Job No.:	T190111D10	Polarization:	Horizontal
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	24VDC
Test item:	Radiation Test	Date:	2019/1/15
Company:	Cermate Technologies Inc.	Time:	下午 06:35:11
Model:	PT2104	Temp.(°C)/Hum.(%)	23(°C)/60%
Description:	Normal Mode	Engineer Signature:	Kevin Chang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	80.4400	57.03	-30.43	26.60	40.00	-13.40	peak	
2	299.6600	50.55	-21.56	28.99	47.00	-18.01	peak	
3	463.5900	48.09	-14.66	33.43	47.00	-13.57	peak	
4	600.3600	44.44	-13.70	30.74	47.00	-16.26	peak	
5	654.6800	42.83	-13.09	29.74	47.00	-17.26	peak	
6	872.9300	44.77	-12.64	32.13	47.00	-14.87	peak	

## 8 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST

#### AC Power




## DC Power



## RADIATED EMISSION TEST Below 1GHz





**Above 1GHz**

## 966 CHAMBER TEST

