

# **FCC 47 CFR PART 15 SUBPART B TEST REPORT**

for

**Industrial Data Gateway**

**MODEL: x-BOX; UNO1032; WISE1032; SxxX32; GxxW32; iCMxx32; ICCxx32;  
EKlxx32; ADAMxx32 (x=A~Z, a~z, 0~9, "-" or blank, any character)**

Test Report Number:

**T160130D09-F**

Issued to:

**Cermate Technologies Inc.**

**7F-1, No.168, Lien Cheng Rd., Chung-Ho District,  
New Taipei City, Taiwan 235**

Issued by:

**Compliance Certification Services Inc.**

**Xindian Lab.**

**No.163-1, Jhongsheng Rd., Xindian Dist.,  
New Taipei City, 23151 Taiwan.**

**TEL: 886-2-22170894**

**FAX: 886-2-22171029**

**Issued Date: February 4, 2016**



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

**Revision History**

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		February 4, 2016		Initial Issue	ALL	Joy Hsiao

**TABLE OF CONTENTS**

<b>1</b>	<b>TEST RESULT CERTIFICATION .....</b>	<b>4</b>
<b>2</b>	<b>EUT DESCRIPTION.....</b>	<b>5</b>
<b>3</b>	<b>TEST METHODOLOGY.....</b>	<b>6</b>
3.1.	DECISION OF FINAL TEST MODE .....	6
3.2.	EUT SYSTEM OPERATION .....	6
<b>4</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>6</b>
4.1.	DESCRIPTION OF SUPPORT UNITS.....	6
4.2.	CONFIGURATION OF SYSTEM UNDER TEST .....	7
<b>5</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1.	FACILITIES .....	8
5.2.	ACCREDITATIONS.....	8
5.3.	MEASUREMENT UNCERTAINTY .....	8
<b>6</b>	<b>CONDUCTED EMISSION MEASUREMENT .....</b>	<b>9</b>
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	9
6.2.	TEST INSTRUMENTS .....	9
6.3.	TEST PROCEDURES.....	10
6.4.	TEST SETUP .....	11
6.5.	DATA SAMPLE .....	11
6.6.	TEST RESULTS .....	12
<b>7</b>	<b>RADIATED EMISSION MEASUREMENT .....</b>	<b>16</b>
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT .....	16
7.2.	TEST INSTRUMENTS .....	17
7.3.	TEST PROCEDURES.....	18
7.4.	TEST SETUP .....	19
7.5.	DATA SAMPLE .....	20
7.6.	TEST RESULTS .....	21
<b>8</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION.....</b>	<b>27</b>
	<b>APPENDIX 1 - PHOTOGRAPHS OF EUT .....</b>	<b>A1-1</b>

# 1 TEST RESULT CERTIFICATION

**Product:** Industrial Data Gateway

**Model:** x-BOX; UNO1032; WISE1032; SxxX32; GxxW32; iCMxx32; ICCxx32; EKlxx32; ADAMxx32 (x=A~Z, a~z, 0~9, "-" or blank, any character)

**Brand:** Cermate

**Applicant:** Cermate Technologies Inc.  
7F-1, No.168, Lien Cheng Rd., Chung-Ho District,  
New Taipei City, Taiwan 235

**Manufacturer:** Cermate Technologies Inc.  
7F-1, No.168, Lien Cheng Rd., Chung-Ho District,  
New Taipei City, Taiwan 235

**Tested:** January 27, 2016 ~ February 3, 2016


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 6-2016 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit

**Note:** 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.  
2. The information of measurement uncertainty is available upon the customer's request.

Deviation from Applicable Standard
None


The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Approved by:**



Sam Hu  
Assistant Manager

**Reviewed by:**



Eva Fan  
Supervisor of report document dept.

## 2 EUT DESCRIPTION

Product	Industrial Data Gateway
Brand Name	Cermate
Model	x-BOX; UNO1032; WISE1032; SxxX32; GxxW32; iCMxx32; ICCxx32; EKlxx32; ADAMxx32 (x=A~Z, a~z, 0~9, "-" or blank, any character)
Applicant	Cermate Technologies Inc.
Housing material	Metal case
Identify Number	T160130D09
Received Date	January 30, 2016
EUT Power Rating	24VDC from Power Supply

### Model Differences

Model Name	Difference	Tested (Check)
S-BOX	Original	<input checked="" type="checkbox"/>
UNO1032; WISE1032	For marketing purpose only	<input type="checkbox"/>
x-BOX; SxxX32; GxxW32; iCMxx32; ICCxx32; EKlxx32; ADAMxx32	1. x=A~Z, a~z, 0~9, "-" or blank, any character 2. For marketing purpose only	<input type="checkbox"/>

### I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. COM 1 Port	1	1
2. COM 2 Port	1	1
3. COM 3 Port	1	1
4. Host (USB) Port	1	1
5. Client (USB) Port	1	1
6. Ethernet Port	2	2
7. SD Slot	1	1

**Note:** Client consigns only one model sample to test (Model Number: S-BOX).

### 3 TEST METHODOLOGY

#### 3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

**Conduction Modes:**

1	AC Power Mode
2	DC Power Mode

**Radiation Mode:**

1	Normal Mode
	Normal Mode / 1-6GHz

**Worst:**

**Conduction:** Mode 2

**Radiation:** Mode 1

#### 3.2. EUT SYSTEM OPERATION

1. Windows 7 boots system
2. Press the start menu, select executive and type ping 192.168.10.10 -t (EUT), ping 192.168.10.100 -t (Server PC).

**Note:** Test program is self-repeating throughout the test.

### 4 SETUP OF EQUIPMENT UNDER TEST

#### 4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

**EUT Devices:**


No.	Equipment	Model No.	Brand Name
1	I/O Board Power Module	B5WR4-2405AS9A	CTC
2	CPU (200MHz)	NUC950ADN	Nuvoton
3	Memory (SDRAM 64M bytes /100MHz)	N/A	CTC

**Peripherals Devices:**

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	USB Mouse	M-U0026	N/A	DOC BSMI: T41126	Logitech	Shielded, 1.8m	N/A
2	Power Supply	DPS-02A-D24	N/A	N/A	Cermate	N/A	Unshielded, 1.8m
3	HMI	PT1070	N/A	N/A	Cermate	LAN: Unshielded, 1.5m COM 2 & COM 3: Shielded, 2.0m COM 1: Shielded, 2.0m	Unshielded, 1.8m
4	DC Power Supply	DPS-02A-D24	N/A	N/A	Cermate	N/A	Unshielded, 1.5m
5	Server PC	T3500	8X36VBX	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m
6	SD Card	N/A	N/A	N/A	PQI	N/A	N/A
7	USB Cable	N/A	N/A	N/A	PQI	Shielded, 1.8m	N/A
8	Ground Cable	N/A	N/A	N/A	N/A	Unshielded, 1.5m	N/A

**Note:**

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

**4.2. CONFIGURATION OF SYSTEM UNDER TEST**

## 5 FACILITIES AND ACCREDITATIONS

### 5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

### 5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>Taiwan</b>	TAF
<b>USA</b>	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>Canada</b>	Industry Canada
<b>Norway</b>	Nemko
<b>Japan</b>	VCCI
<b>Taiwan</b>	BSMI
<b>USA</b>	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

### 5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	$\pm 1.59$
Radiated emissions	30MHz ~ 1000MHz	$\pm 4.12$
	1000MHz ~ 18000MHz	$\pm 4.74$
	18000MHz ~ 26000MHz	$\pm 3.03$
	26000MHz ~ 40000MHz	$\pm 3.38$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be based on the results of the compliance measurement. Consequently the measured emissions being less than the maximum allowed emission result in this being a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is based on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.6dB and 5.2dB respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.



## 6 CONDUCTED EMISSION MEASUREMENT

### 6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 6.2. TEST INSTRUMENTS

Conducted Emission room # A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TEST RECEIVER	R&S	ESCI	101201	08/21/2016
LISN (EUT)	SCHWARZBECK	NSLK 8127	8127527	08/23/2016
LISN	SCHWARZBECK	NSLK 8127	8127526	08/23/2016
BNC CABLE	EMCI	CFD300-NL	BNC#A8	05/19/2016
Pulse Limiter	R&S	ESH3Z2	SD-C002	08/23/2016
THERMO-HYGRO METER	WISEWIND	201A	No. 02	05/10/2016
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. N.C.R = No Calibration Request.


**6.3. TEST PROCEDURES** (please refer to measurement standard or CCS SOP PA-031)**Procedure of Preliminary Test**

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC 120VAC/60Hz main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

**Procedure of Final Test**

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

## 6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1


Freq.	= Emission frequency in MHz
Reading	= Uncorrected Analyzer/Receiver reading
Factor	= Insertion loss of LISN + Cable Loss + Pulse Limit
Result	= Reading + Factor
Limit	= Limit stated in standard
Margin	= Reading in reference to limit
P	= Peak Reading
Q	= Quasi-peak Reading
A	= Average Reading
L1	= Hot side
L2	= Neutral side

### Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

## 6.6. TEST RESULTS


Model No.	S-BOX	6dB Bandwidth	9 kHz
Environmental Conditions	21°C, 64% RH	Test Mode	Mode 1
Tested by	Frank Liao	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2140	36.08	10.07	46.15	79.00	-32.85	P	L1
0.2620	38.62	10.08	48.70	79.00	-30.30	P	L1
0.4260	35.67	10.09	45.76	79.00	-33.24	P	L1
0.8500	32.90	10.11	43.01	73.00	-29.99	P	L1
1.4860	36.42	10.16	46.58	73.00	-26.42	P	L1
22.5459	45.84	11.39	57.23	73.00	-15.77	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


<b>Model No.</b>	S-BOX	<b>6dB Bandwidth</b>	9 kHz
<b>Environmental Conditions</b>	21°C, 64% RH	<b>Test Mode</b>	Mode 1
<b>Tested by</b>	Frank Liao	<b>Phase</b>	L2
<b>Standard</b>	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2140	36.21	10.07	46.28	79.00	-32.72	P	L2
0.2620	38.44	10.08	48.52	79.00	-30.48	P	L2
0.3180	35.01	10.09	45.10	79.00	-33.90	P	L2
0.4260	35.51	10.09	45.60	79.00	-33.40	P	L2
1.4860	36.25	10.16	46.41	73.00	-26.59	P	L2
22.5180	46.25	11.39	57.64	73.00	-15.36	P	L2

**Note:** 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


<b>Model No.</b>	S-BOX	<b>6dB Bandwidth</b>	9 kHz
<b>Environmental Conditions</b>	25°C, 58% RH	<b>Test Mode</b>	Mode 2 / Worst
<b>Tested by</b>	Frank Liao	<b>Phase</b>	L1
<b>Standard</b>	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
1.1220	50.96	10.13	61.09	73.00	-11.91	P	L1
1.1260	46.91	10.13	57.04	60.00	-2.96	A	L1
1.9580	50.70	10.21	60.91	73.00	-12.09	P	L1
1.9660	47.33	10.21	57.54	60.00	-2.46	A	L1
2.8100	50.07	10.24	60.31	73.00	-12.69	P	L1
2.8100	44.20	10.24	54.44	60.00	-5.56	A	L1
3.0020	50.54	10.25	60.79	73.00	-12.21	P	L1
3.0980	40.22	10.25	50.47	60.00	-9.53	A	L1
3.6540	50.93	10.27	61.20	73.00	-11.80	P	L1
3.6540	42.08	10.27	52.35	60.00	-7.65	A	L1
4.4980	52.26	10.30	62.56	73.00	-10.44	P	L1
4.5020	36.29	10.31	46.60	60.00	-13.40	A	L1
5.8940	36.99	10.37	47.36	60.00	-12.64	A	L1
5.9980	50.35	10.39	60.74	73.00	-12.26	P	L1

**Note:** 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

<b>Model No.</b>	S-BOX	<b>6dB Bandwidth</b>	9 kHz
<b>Environmental Conditions</b>	25°C, 58% RH	<b>Test Mode</b>	Mode 2 / Worst
<b>Tested by</b>	Frank Liao	<b>Phase</b>	L2
<b>Standard</b>	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.5580	47.79	10.09	57.88	60.00	-2.12	A	L2
0.5620	50.01	10.09	60.10	73.00	-12.90	P	L2
1.1220	50.04	10.12	60.16	73.00	-12.84	P	L2
1.1220	46.32	10.12	56.44	60.00	-3.56	A	L2
1.9540	46.69	10.19	56.88	60.00	-3.12	A	L2
1.9620	50.81	10.19	61.00	73.00	-12.00	P	L2
2.7900	47.37	10.22	57.59	60.00	-2.41	A	L2
2.8060	50.97	10.22	61.19	73.00	-11.81	P	L2
3.6260	52.29	10.24	62.53	73.00	-10.47	P	L2
3.6260	47.81	10.24	58.05	60.00	-1.95	A	L2
4.4620	38.22	10.27	48.49	60.00	-11.51	A	L2
4.5020	52.00	10.30	62.30	73.00	-10.70	P	L2
5.8660	38.03	10.35	48.38	60.00	-11.62	A	L2
5.9980	50.44	10.36	60.80	73.00	-12.20	P	L2

**Note:** 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

## 7 RADIATED EMISSION MEASUREMENT

### 7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

**NOTE:** (1) The lower limit shall apply at the transition frequencies.  
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 (3) The measurement above 1GHz is at close-in distances 3m, and determine the limit  $L_2$  corresponding to the close-in distance  $d_2$  by applying the following relation:  $L_2 = L_1 (d_1/d_2)$ , where  $L_1$  is the specified limit in microvolts per metre (uV/m) at the distance  $d_1$  (10m),  $L_2$  is the new limit for distance  $d_2$  (3m).  
 So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80



According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

## 7.2. TEST INSTRUMENTS

Open Area Test Site # H				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	101340	04/07/2016
BilogAntenna	Sunol	JB1	A061711	08/05/2016
Pre-Amplifier	HP	8447D	1937A01554	10/01/2016
CABLE	EMCI	CFD400-E	N-Type#H10	04/08/2016
Thermo-Hygro Meter	Wisewind	201A	No. 03	06/02/2016
Test S/W	EZ-EMC			
Above 1GHz Used				
Signal Analyzer (9k – 44GHz)	Agilent	N9010A	MY53440125	12/13/2016
Horn Antenna (1 – 18GHz)	EMCO	3117	00139062	10/21/2016
Pre-Amplifier (1 – 26.5GHz)	HP	8449B	3008A01266	12/13/2016
CABLE (1 – 18GHz)	Rosnol	A1K50-EW0630	151126-1	12/20/2016
THERMO- HYGRO METER	WISEWIND	201A	No. 02	05/10/2016
Test S/W	EZ-EMC			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.

**7.3. TEST PROCEDURES** (please refer to measurement standard or CCS SOP PA-031)**Procedure of Preliminary Test**


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

**Procedure of Final Test**


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

## 7.4. TEST SETUP

### Below 1GHz



### Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 7.5. DATA SAMPLE

### Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

### Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz  
Reading = Uncorrected Analyzer/Receiver reading  
Factor = Antenna Factor + Cable Loss - Amplifier Gain  
Result = Reading + Factor  
Limit = Limit stated in standard  
Margin = Reading in reference to limit  
P = Peak Reading  
Q = Quasi-peak Reading  
A = Average Reading  
H = Antenna Polarization: Horizontal  
V = Antenna Polarization: Vertical


### Calculation Formula

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

## 7.6. TEST RESULTS

### Below 1GHz

<b>Model No.</b>	S-BOX	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	16°C, 80% RH	<b>6dB Bandwidth</b>	120 kHz
<b>Antenna Pole</b>	Vertical	<b>Antenna Distance</b>	10m
<b>Detector Function</b>	Quasi-peak.	<b>Tested by</b>	David Cheng
<b>Standard</b>	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		



Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
95.9100	50.00	-16.92	33.08	40.00	-6.92	100	108	Q	V
137.2400	42.00	-12.48	29.52	40.00	-10.48	100	52	Q	V
250.0100	53.50	-13.23	40.27	47.00	-6.73	100	97	Q	V
375.0280	51.10	-9.91	41.19	47.00	-5.81	100	146	Q	V
500.0280	41.90	-6.78	35.12	47.00	-11.88	400	331	Q	V
750.0100	35.50	-2.27	33.23	47.00	-13.77	400	214	Q	V

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

<b>Model No.</b>	S-BOX	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	16°C, 80% RH	<b>6dB Bandwidth</b>	120 kHz
<b>Antenna Pole</b>	Horizontal	<b>Antenna Distance</b>	10m
<b>Detector Function</b>	Quasi-peak.	<b>Tested by</b>	David Cheng
<b>Standard</b>	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
125.0100	35.60	-12.30	23.30	40.00	-16.70	400	71	Q	H
250.0160	54.70	-13.23	41.47	47.00	-5.53	400	312	Q	H
375.0200	50.40	-9.91	40.49	47.00	-6.51	400	228	Q	H
500.0300	42.50	-6.78	35.72	47.00	-11.28	100	45	Q	H
625.0100	35.70	-4.54	31.16	47.00	-15.84	100	138	Q	H
750.0300	30.70	-2.27	28.43	47.00	-18.57	100	99	Q	H

**Note:** 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

## Above 1GHz


Model No.	S-BOX	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical	Antenna Distance	3m
Highest frequency generated or used	200MHz	Upper frequency	6000MHz
Detector Function	Peak and average.	Tested by	Frank Liao
Standard	FCC CLASS A		



Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1066.667	52.83	-8.77	44.06	80.00	-35.94	P	V
1150.000	54.48	-8.60	45.88	80.00	-34.12	P	V
1483.333	51.12	-7.91	43.21	80.00	-36.79	P	V
2000.000	49.08	-3.39	45.69	80.00	-34.31	P	V
2150.000	50.03	-3.18	46.85	80.00	-33.15	P	V
2800.000	49.84	-2.36	47.48	80.00	-32.52	P	V

Note: 1. P= Peak Reading; A= Average Reading.

<b>Model No.</b>	S-BOX	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	26°C, 60% RH	<b>6dB Bandwidth</b>	1 MHz
<b>Antenna Pole</b>	Horizontal	<b>Antenna Distance</b>	3m
<b>Highest frequency generated or used</b>	200MHz	<b>Upper frequency</b>	6000MHz
<b>Detector Function</b>	Peak and average.	<b>Tested by</b>	Frank Liao
<b>Standard</b>	FCC CLASS A		




Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1083.333	52.90	-8.73	44.17	80.00	-35.83	P	H
1141.667	51.95	-8.61	43.34	80.00	-36.66	P	H
1266.667	51.61	-8.36	43.25	80.00	-36.75	P	H
1416.667	50.47	-8.05	42.42	80.00	-37.58	P	H
2000.000	50.43	-3.39	47.04	80.00	-32.96	P	H
2441.667	48.80	-2.75	46.05	80.00	-33.95	P	H

**Note:** 1. P= Peak Reading; A= Average Reading.




## 966 Chamber Test Data

Job No.:	T160130D09	Polarization:	Vertical
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	120VAC/60Hz
Test item:	Radiation Test	Date:	2016/1/27
Company:	Cermate Technologies Inc.	Time:	11:41:27
Model:	S-BOX	Temp.(°C)/Hum.(%):	26(°C)/60%
Description:	Normal Mode	Engineer Signature:	Frank Liao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	97.8570	54.70	-21.25	33.45	40.00	-6.55	QP	
2	97.9000	60.88	-21.24	39.64	40.00	-0.36	peak	
3	137.6700	63.38	-20.94	42.44	40.00	2.44	peak	
4	137.7710	59.90	-20.93	38.97	40.00	-1.03	QP	
5	250.1900	56.18	-21.43	34.75	47.00	-12.25	peak	
6	375.3200	56.67	-19.78	36.89	47.00	-10.11	peak	
7	500.4500	51.49	-15.23	36.26	47.00	-10.74	peak	
8	750.7100	46.51	-10.89	35.62	47.00	-11.38	peak	

Job No.:	T160130D09	Polarization:	Horizontal
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	120VAC/60Hz
Test item:	Radiation Test	Date:	2016/1/27
Company:	Cermate Technologies Inc.	Time:	11:47:04
Model:	S-BOX	Temp.(°C)/Hum.(%)	26(°C)/60%
Description:	Normal Mode	Engineer Signature:	Frank Liao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	97.9000	55.21	-28.05	27.16	40.00	-12.84	peak	
2	137.6700	49.61	-23.02	26.59	40.00	-13.41	peak	
3	250.1900	54.96	-23.68	31.28	47.00	-15.72	peak	
4	375.0169	64.60	-19.00	45.60	47.00	-1.40	QP	
5	375.3200	64.49	-19.01	45.48	47.00	-1.52	peak	
6	500.4500	53.01	-13.71	39.30	47.00	-7.70	peak	
7	625.5800	43.38	-13.08	30.30	47.00	-16.70	peak	

## 8 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST




## **RADIATED EMISSION TEST**

### **Below 1GHz**





## Above 1GHz



## 966 CHAMBER TEST

